

#### TECHNICAL SUPPORT

We pride ourselves in providing high quality services and technical support to all customers.

#### CONTACT INFORMATION

For more information on any of our products or services, please contact us at:

Golden Eagle Extrusions, Inc.

1762 State Route 131

Milford, Ohio 45150

P - 800.634.3355

F - 513.248.8300

[www.goldeneagleextrusions.com](http://www.goldeneagleextrusions.com)

[info@goldeneagleextrusions.com](mailto:info@goldeneagleextrusions.com)

# LFO-160HD LIDDING FILM

## TECHNICAL DATA SHEET

Golden Eagles LFO-160HD lidding film is an Oriented Polypropylene laminated to a Metallocene extrusion. This material is designed for use with HDPE trays or trays with a LLDPE laminate seal layer.

**GAUGE:** .002 (custom thicknesses available)

**OTR:** 160 cc / 100 sq. in. / 24 hours

**CO<sub>2</sub>:** 640 cc / 100 sq. in. / 24 hours

**MVTR:** .25 gr. / 100 sq. in. / 24 hours

**FDA STATUS:** LFO-160HD is manufactured from resins approved for food contact by the FDA.

### SEALING TEMPERATURES:

Golden Eagles LFO-160HD can be sealed for optimal adhesion at 320°F, with a dwell time of 3 seconds.

*\*Values shown above are typical and are not for use as final limiting specifications.*