

TECHNICAL SUPPORT

We pride ourselves in providing high quality services and technical support to all customers.

CONTACT INFORMATION

For more information on any of our products or services, please contact us at:

Golden Eagle Extrusions, Inc.

1762 State Route 131

Milford, Ohio 45150

P - 800.634.3355

F - 513.248.8300

www.goldeneagleextrusions.com

info@goldeneagleextrusions.com

LFO-160P LIDDING FILM

TECHNICAL DATA SHEET

Golden Eagles LFO-160P lidding film is an Oriented Polypropylene laminated to a LLDPE/EMA blend. This material is designed for use as a peelable lidding structure, and will adhere to multiple substrates.

GAUGE: .002 (*custom thicknesses available*)

YIELD: 14.8 *msi/lb.*

HAZE: 25%

OTR: 160 cc / 100 sq. in. / 24 hours

CO²: 640 cc / 100 sq. in. / 24 hours

MVTR: .25 gr. / 100 sq. in. / 24 hours

FDA STATUS: *LFO-160P is manufactured from resins approved for food contact by the FDA.*

Disclaimer: *Nothing in this data sheet is to be taken as a warranty. Offered for your consideration only, the information provided herein represents our best knowledge and judgment. Golden Eagle Extrusions, Inc. assumes no liability whatsoever in connection with the use of this information.*