

## LIDDING FILMS



### TECHNICAL SUPPORT

We pride ourselves in providing high quality services and technical support to all customers.

### CONTACT INFORMATION

For more information on any of our products or services, please contact us at:

Golden Eagle Extrusions, Inc.  
1762 State Route 131  
Milford, Ohio 45150  
P - 800.634.3355  
F - 513.248.8300

[www.goldeneagleextrusions.com](http://www.goldeneagleextrusions.com)  
[info@goldeneagleextrusions.com](mailto:info@goldeneagleextrusions.com)

# LFO-4AP

## STANDARD THICKNESS - 92 GAUGE

**LFO-4AP** is a heat sealable lidding film with a specialty sealant on a PET substrate designed for tight to lock seal of a variety of trays.

### Key Features

- Good moisture and oxygen barrier
- Suitable for "see through" packaging structure
- One side sealable
- For printing and laminating in packaging structures

PROPERTIES	UNIT	TESTING METHOD	TYPICAL VALUES
<b>MECHANICAL</b>			
Tensile Strength MD TD	lb/in <sup>2</sup>	ASTM D882	36,000 39,000
Elongation MD TD	%	ASTM D882	150 130
<b>PHYSICAL</b>			
Yield	in <sup>2</sup> /lb		21,500
COF Sealant side Heat resistant side		ASTM D1894	03 0.3
Haze	%	ASTM D1003	3.5
<b>BARRIER</b>			
MVTR	g/100 in <sup>2</sup> /day	ASTM F1249 38°C, 100%RH	1.5
OTR	cc/100 in <sup>2</sup> /day	ASTM D3985 23°C, 0%RH	4.0
<b>THERMAL</b>			
Shrinkage MD TD	%	ASTM D1204	1.6 0.3

**Disclaimer:** Nothing in this data sheet is to be taken as a warranty. Offered for your consideration only, the information provided herein represents our best knowledge and judgment. Golden Eagle Extrusions, Inc. assumes no liability whatsoever in connection with the use of this information.