

## LIDDING FILMS



### TECHNICAL SUPPORT

We pride ourselves in providing high quality services and technical support to all customers.

### CONTACT INFORMATION

For more information on any of our products or services, please contact us at:

Golden Eagle Extrusions, Inc.  
1762 State Route 131  
Milford, Ohio 45150  
P - 800.634.3355  
F - 513.248.8300

[www.goldeneagleextrusions.com](http://www.goldeneagleextrusions.com)  
[info@goldeneagleextrusions.com](mailto:info@goldeneagleextrusions.com)

# LFO-6APET

## STANDARD THICKNESS - 2.2 MIL

**LFO-6APET** is a heat sealable lidding film with a specialty sealant on a PET substrate designed for tight to lock seal of a variety of trays. This film is laminated to a 92 GA PET top layer.

### Key Features

- Good moisture and oxygen barrier
- One side sealable
- Tight, lock seal to PET substrates

PROPERTIES	UNIT	TESTING METHOD	TYPICAL VALUES
PHYSICAL			
Yield	in <sup>2</sup> /lb		9,200
COF Sealant side		ASTM D1894	0.3
Heat resistant side			0.55
BARRIER			
MVTR	g/100 in <sup>2</sup> /day	ASTM F1249 38°C, 100%RH	0.5
OTR	cc/100 in <sup>2</sup> /day	ASTM D3985 23°C, 0%RH	3.30
THERMAL			
Shrinkage			
MD	%	ASTM D1204	1.7
TD			0.3

**Disclaimer:** Nothing in this data sheet is to be taken as a warranty. Offered for your consideration only, the information provided herein represents our best knowledge and judgment. Golden Eagle Extrusions, Inc. assumes no liability whatsoever in connection with the use of this information.